



**Paints**

# Fast Dry Acrylic Latex Primer/ Undercoat - Grey

5813

## DESCRIPTION

---

Fast Dry Acrylic Latex Primer/ Undercoat – Grey a fast dry high solid high quality 100% acrylic latex coating designed for kiln dried Spruce, Pine, Alpine Fir wood products.

## FEATURES

---

- Excellent hiding characteristics and dries to a flat finish for ease of top coating.
- Provides good protection for factory produced wood products before installation in the field.
- Low VOC
- Water clean up

## APPROVALS

---

Pending.

## COLOR AVAILABILITY

---

Fast Dry Acrylic Latex Primer/ Undercoat is available in a neutral grey colour.

## SPECIFICATION DATA

---

**Spread Rate:** 16 sq.metres/litre  
@ 1 mil D.F.T. (Theoretical)

**Sheen:** Flat  
**Thinner:** Not Required.  
**Clean Up:** Soap & water  
**Dry Time ( 24°C & 50% R.H. ):**  
**Tack Free:** 15 minutes  
**Recoat:** 1 hour  
**Cure:** 7-10 Days

**Resin Type:** 100% Acrylic  
**Solids % by Weight:** 67

**Solids % by Volume:** 45

**Specific Gravity:** N/A  
**Viscosity:** 93 -98 KU  
**Flash Point:** N/A  
**Specular Gloss:** 0 – 10 @ 60°  
**Sag Rating:** N/A

**Recommended Film Thickness:**  
Wet – 3.3 to 4.4 mils  
Dry – 1.5 to 2.0 mils

## INTENDED USES

---

**Fast Dry Acrylic Latex Primer/ Undercoat** is a pre-prime coating for exterior wood, facia board, siding, and doors.

## SURFACE PREPARATION

---

**DRYWALL or PLASTER:** Not Recommended

**PAINTED SURFACES:** Not Recommended

**BARE WOOD:** Smoothly sand bare wood to remove all loose fibers. Surface to be coated must be dry and free of dirt, sanding dust, oils and mildew.

**METAL:** Not Recommended.

**CONCRETE or MASONRY:** Not Recommended.

## APPLICATION

---

Mix thoroughly before use. Apply by brush, roller or spray. Spray application for best results. Use as is do not thin. Allow 1 hour to dry between coats. Apply only if temperature is above 10°C (50°F). Avoid painting in direct sun light and exposure to water for 24 hours after application.

**Coverage:** Up to 125 sq. ft. (11.6sq. m.) per litre (1L)

**Dry time:** Dries to touch in 15 minutes, allow 1 hour between coats. Low temperatures or high humidity may affect times.

**Brush** - Polyester/ Nylon Synthetic Bristles – Small Areas only

**Roller** - 10 mm to 20 mm Lint Free

**Airless Spray** - 0.015" to 0.021" tip size  
- 1700 to 2700 p.s.i. pressure

Spray recommendations may vary dependant upon equipment manufacturer.

**Clean up:** Soap & warm water.

## GUARANTEE

---

ICI guarantees performance of this product if it is properly applied in accordance with label directions. Should this product fail to meet this guarantee, ICI will at your option, upon proof of purchase, provide replacement paint free of charge or refund the full purchase price. No other guarantee expressed or implied, statutory or otherwise, is given.

**THIS GUARANTEE SPECIFICALLY EXCLUDES LABOUR OR COST OF LABOUR FOR THE APPLICATION OF ANY PAINT.**

Complete product and application information is available upon request.

## SPECIAL INFORMATION

---

All mentioned specifications refer to Fast Dry Acrylic Latex Primer /Undercoat 5813 Grey

**KEEP FROM FREEZING.**

**Date of Issue: November 17, 2009**

**VOC/VOS Statement: (prior to tinting)**

This product contains a maximum of 25 grams/ VOC per litre of coating.

---

**CAUTION: USE WITH GOOD VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID TREATMENT: IF SWALLOWED, CALL A PHYSICIAN OR POISON CONTROL**

**CENTRE IMMEDIATELY. For Emergency information call 1-800-545-2643.**

**DISPOSAL: THIS PRODUCT MUST BE DISPOSED OF AT A HAZARDOUS WASTE DISPOSAL SITE, CHECK YOUR YELLOW PAGES FOR YOUR NEAREST SITE OR CONTACT YOUR MUNICIPAL /PROVINCIAL GOVERNMENT WASTE SERVICE FOR MORE INFORMATION.**

---



**Paints**

**ICI Canada Inc**

**8200 Keele St, Concord, ON, Canada L4K 2A5**

**Bus.: (905) 669-1020 / Fax: (905) 669-3433**

### LIMITATION OF LIABILITY

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to our specifications. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOUR OR COST OF LABOUR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.